HARATI
SECURITY

"Amazing Speed, we are loving it!"

HS-76-RFC

More Capacity and Wireless Connection

Introduction

HS-76-RFC is a face identification T&A terminal with face, PIN and RFID recognition modes. With the latest face identification algorithm and streamlined technology, it can hold 400 face templates without dividing into groups and complete verification in less than 1 second. Communicating via Wi-Fi, Ethernet, and USB (host and client), it can ensure a smooth connection and data transfer. All the settings can be easily done on 3-inch TFT touch screen. It has been elaborately designed and finely processed to match your slap-up office perfectly.

Features:

* Elegant ergonomic design.
* Wi-Fi, Ethernet, and USB (host and client) communication.
* 3-inch TFT touch screen, T9 Input, and 9 Digit User ID.
* Infra-red optical system enables user-identification in
  poorly lit environment.
* Optional Mifare card module.
* Professional face identification algorithm.

Specifications:

Display	3-inch Touch Screen
Face Capacity	400(1:N)
ID Card Capacity	10,000
Logs Capacity	100,000
Communication	Wi-Fi, Ethernet , USB (host and client)
Standard Functions	ID card,Automatic Status Switch, Self-Service Query, Work Code, T9 Input, 9 Digit User ID, DLST,Scheduled-bell and Short Message.
Optional Function	Mifare Card.
Power Supply	12V/1.5A
Verification Speed	≤1S
Operating Temperature	0℃-45℃
Operating Humidity	20%-80%
Dimensions	104.70(L)*160.00(H)*36.00(W) mm

Configuration:

PC

HUB

USB Client

Wi-Fi

Ethernet

USB Key

HS-76-RFC