



HS6000-8F Wireless & Wired Compatible Solution

HS6000-8F is compatible with wire and wireless transmits alarm messages to users via telephone communication network and is capable of achieving remote control and dealing with emergencies. It simplifies your life and makes your site and property safer by protecting you 24 hours a day with flexible configuration and easy operation.



It can not only alarm networking, but also standalone. User can dial the center to arm or disarm.

Specification

- HS6000-8F:16 fully programmable zones, 8 wireless and 8 wired.
- MCU control, keypad programming, LED display.
- Flexible programming operation.
- Flexible configures: fitting of different detectors available.
- Anti-tamper for master control and keypad can extend 2 wire programmed zones.
- Mater control automatically dials alarm center, user's mobile telephone or unmoved telephone with voice announcement of system status as soon as the system alarms.
- 40 event log for query.
- Compatible with ADEMCO contract; not only networking alarm, but also stand alone alarm.
- 3 group automatic timing for arming/ disarming.
- Malfunction alarm for low battery voltage, AC power loss and telephone line loss.
- Record personal address message by users.
- Wireless frequency: 315MHZ/433MHZ/868MHZ.

Technical Parameters

- Mainframe enclosure: 274mmx264x86mm
- Keypad size: 155mmx95mmx28mm
- Rated operation current: 220V AC
- Static operation current: 120mA
- Back-up battery (not included):12V, 7AH sealed lead - acid accumulator
- Bell output: 10.5-13.5VDC/0.5A
- Operation temperature: -100C~+550C
- Wireless working distance : 100m (no obstacle)
- Wireless frequency: 315MHZ/433MHZ/868MHZ