

## HS8003-DW

The HS8003-DW is an innovative all-in-one hi class wireless solution for residential and commercial facilities. It provides a complete solution for all aspects of security and connectivity covering a full range of wireless accessories working seamlessly.

Activating periodic supervision for accessories, it ensures system safety. Featuring PSTN, GSM dialing or SMS sending optional, it offers multiple performance options and flexibility. With upload and download software and interface, you can load the data and remote program the system. It meets different ranges of demand to personal phones or central station by easy programming and simple menu-operation with voice guide.



All-in-one Hi-class Wireless Solution

### Specification

- 16 wireless zones and 2 wired zones.
- TFT LCD with menu display, intelligent voice-guide operation.
- Periodic supervision accessories.
- PSTN or GSM dialing or SMS message send for alarm optional.
- 255 event buffer.
- Built-in tamper and rear tamper for control panel.
- Compatible with built-in siren (85dB), wired external siren and 3 wireless sirens.
- 1 PGM and AUX power output.
- 2 central stations working selectable.
- 6 phone numbers: 2 for CMS and 4 for personal phones (mobiles).
- 8 codes: 1 for installer, 1 for master, 1 for temporary, 1 for duress and 4 for users.
- Available with utmost 6 remote controller.
- Compatible with Contact ID protocol.
- Wireless frequency: 433MHZ/868MHZ.

### Technical Parameters

- Power adapter: Input 100-240VAC 50/60HZ, output 12VDC 1.5A
- Operating voltage of the control panel: 12VDC
- Backup battery capacity: 7.2V/1800mAh
- Static operating current:  $\leq 90\text{mA}@12\text{V}$
- AUX power output: AC 10-12V, DC6-8V
- Siren output current:  $\leq 400\text{mA}$
- PGM output max load: C50V/50mA
- Built-in siren: 85dB